

EFA L

The safety ladder for quick application in chemical or electrical environments.

Product description

- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Outside width: 420 mm - particularly stable.



Product features

Load: max. 150 kg
 Material: Glass-fibre reinforced plastic
 Pitch rung/tread: 265 mm
 Producttype: GRP single ladder with rungs
 Tread depth: 30 mm
 Type rung/tread: serrated

Hints and special features

in accordance with DIN EN 131-1, order No. 41255 includes a stabiliser bar.
 Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Overall length	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
41251	6	1.92 m	58 mm	1.924 mm × 430 mm × 70 mm	5.6 kg		2.8 m
41253	10	2.993 m	58 mm	3.044 mm × 430 mm × 70 mm	8.6 kg		3.85 m
41255	14	4.16 m	73 mm	4.164 mm × 430 mm × 70 mm	12.4 kg	0.9 m	4.95 m